

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Demodox 110 (Old blue)

· Article number: 1899900-03

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the preparation

Metal surface treatment

Paint

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Alfa Laval Tumba AB
Hans Stahles väg 7
S-147 80 TUMBA
SWEDEN

sds.question@alfalaval.com

- · Further information obtainable from: sds.question@alfalaval.com
- · 1.4 Emergency telephone number:

For immediate, life-threatening emergencies, call 999

For health advice and information (24h) dial 111 (NHS direct)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC

R10-66-67: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to EU guidelines:

The product has been marked in accordance with EU Directives / respective national laws.

- · Risk phrases:
- 10 Flammable.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- · Safety phrases:

16 Keep away from sources of ignition - No smoking.

(Contd. on page 2)



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

(Contd. of page 1)

- 24 Avoid contact with skin.
- 33 Take precautionary measures against static discharges.
- 60 This material and its container must be disposed of as hazardous waste.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R10-66-67 Flam. Liq. 3, H226; STOT SE 3, H336	25-50%
CAS: 1330-20-7	xylene Xn R20/21; Xi R38; F R11 Flam. Liq. 2, H225; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate 9 R10 Flam. Liq. 3, H226	
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Xn R20; F R11 Flam. Liq. 2, H225; Acute Tox. 4, H332	≤ 2.5%

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Take affected persons out into the fresh air.

- After inhalation: Supply fresh air: consult doctor in case of complaints.
- · After skin contact:

Take off immediately all contaminated clothing.

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Remove contact lenses, if present and easy to do. Continue rinsing.

· After swallowing:

Rinse out mouth and then drink plenty of water.

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

(Contd. of page 2)

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Do not breathe vapour.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

When using do not eat, drink or smoke.

Keep receptacles tightly sealed.

Avoid contact with skin and eyes.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Keep away from heat and direct sunlight.

Store in cool, dry conditions in well sealed receptacles.

· Information about storage in one common storage facility:

Do not store together with oxidizing and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Store under lock and key and with access restricted to technical experts or their assistants only.

· 7.3 Specific end use(s)

Paint

Restricted to professional users.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

dients with limit values that require monitoring at the workplace:
36-4 n-butyl acetate
Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
-20-7 xylene
Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk, BMGV
55-6 2-methoxy-1-methylethyl acetate
Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk
11-4 ethylbenzene
Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

· DNELs

123-86-4 n-butyl acetate: Hazard via inhalation route: Long term exposure: 480 mg/ m³, Hazard assessment conclusion: DNEL.

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

(Contd. of page 4)

1330-20-7 Xylene: Hazard via inhalation route: Long term exposure: 77 mg/m3, Hazard assessment conclusion: DNEL, Most sensitive endpoint: Repeated dose toxicity, Overall assessment factor: 3, Dose descriptor starting point: NOAEC.

108-65-6 2-methoxy-1-methylethyl acetate: Hazard via inhalation route: Long term exposure: 275 mg/m³, Hazard assessment conclusion: DNEL, Most sensitive endpoint: Irritation (respiratory tract), Overall assessment factor: 6, Dose descriptor starting point: LOAEC.

100-41-4 Ethylbenzene: Hazard via inhalation route: Long term exposure: 77 mg/m3, Hazard assessment conclusion: DNEL, Most sensitive endpoint: Repeated dose toxicity, Overall assessment factor: 3, Dose descriptor starting point: NOAEC.

· PNECs

123-86-4 n-butyl acetate: Aqua (freshwater): 0,18 mg/L, Assessment factor: 100, Extrapolation method: Assessment factor.

1330-20-7 Xylene: Aqua (freshwater): 0,327 mg/L, Assessment factor: 1, Extrapolation method: Statistical extrapolation.

108-65-6 2-methoxy-1-methylethyl acetate: Aqua (freshwater): 0,635 mg/L, Assessment factor: 100, Extrapolation method: Assessment factor.

100-41-4 Ethylbenzene: Aqua (freshwater): 0,1 mg/L, Assessment factor: 10, Extrapolation method: Assessment factor.

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Use only in well-ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

Keep away from foodstuffs, beverages and feed.

Ground/bond container and receiving equipment.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber (Viton)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

· Eye protection:

(Contd. of page 5)



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical ar	id chemical properties
General Information	
· Appearance:	
Form:	Viscous

Colour: Blue
Odour: Solvent-like
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: 124 ℃

· Flash point: 29 ℃

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 370 $^{\circ}$ C

· Decomposition temperature: Not determined.

· Self-igniting: 420 °C

• **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol % **Upper:** 7.5 Vol %

· Vapour pressure at 20 °C: 10.7 hPa

Density at 20 °C:
 Relative density
 Vapour density

Not determined.
Net determined.

Vapour densityEvaporation rateNot determined.Not determined.

· Solubility in / Miscibility with

water: Not determined.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 7)



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

(Contd. of page 6)

· Viscosity:

Dynamic: Not determined.

Kinematic at 23 °C: 120-140 s (DIN CUP 4 MM)

· Solvent content:

Organic solvents: 65.0 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents.
- 10.4 Conditions to avoid

High heat

Keep away from sources of ignition - No smoking.

· 10.5 Incompatible materials:

Store away from oxidizing agents.

Keep away from acids.

Do not store together with alkalis (caustic solutions).

• 10.6 Hazardous decomposition products: No further information, refer to section 5.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute tox	icity:	
123-86-4 ı	n-butyl ac	etate
Oral	LD50	13100 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21.0 mg/l (rat)
1330-20-7	xylene	
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
108-65-6 2	2-methoxy	v-1-methylethyl acetate
Oral	LD50	8532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
100-41-4	ethylbenze	ene
Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)
		(Contd. on page 9

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

(Contd. of page 7)

· Primary irritant effect:

• on the skin: No irritant effect. • on the eye: Irritating effect.

· Sensitization: No sensitizing effects known.

· Other information (about experimental toxicology):

If the product is overheated, fumes and vapors may be irritating to the upper respiratory tract and lungs.

Additional toxicological information:

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

· Repeated dose toxicity Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

· European waste catalogue

The European Waste Catalogue (EWC) waste codes do not refer to product but to origin. The manufacturer is therefore unable to quote a waste code for products which are used in various industries. Any codes shown should be regarded as a recommendation to the user.

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF
	COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES,
	SEALANTS AND PRINTING INKS
08 01 00	wastes from MESU and removal of paint and varnish

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 00 00 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

(Contd. of page 8)

15 01 00 packaging (including separately collected municipal packaging waste)

15 01 10* packaging containing residues of or contaminated by dangerous substances

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information	on
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):EMS Number:	30 F-E, <u>S-E</u>
· 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Transport category	3
· Tunnel restriction code	D/E

- GB



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 05.09.2013 Version number 5 Revision: 05.09.2013

Trade name: Demodox 110 (Old blue)

(Contd. of page 9)

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) no.1907/2006 (REACH)

EU regulation (EC) no 1272/2008 (CLP)

EC DIRECTIVE 2008/98/EC (waste)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. LIMITATION OF LIABILITY

This document is only intended to be used as guidance as regards the risks of which we are aware that are associated with the product. Every individual who works with the product or in close proximity of it must receive suitable training. Individuals who come into contact with the product must be capable of using their own judgement as regards conditions or methods for handling, storing and using the product. Alfa Laval is not liable for demands, losses or damage of any kind that arise from flaws or deficiencies in this document or from using, handling, storing or disposing of the product unless it can be proven that Alfa Laval has acted in a grossly negligent manner. Beyond what has been agreed upon and specified in writing with Alfa Laval in the individual case, Alfa Laval makes no promises or assumes any liability, including but not limited to implicit guarantees regarding marketability or appropriateness in terms of both the information provided in this document and the product to which the information refers.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R38 Irritating to skin.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: MACC -Materials & Chemistry Centre
- * Data compared to the previous version altered.