

Page 1/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

## 1 Identification

· Product identifier

· Trade name: GC6B / GC4

· Article number: 32220-3055-5

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Adhesives

· Details of the supplier of the safety data sheet

· Supplier:

Alfa Laval Technologies AB

SE-221 00 Lund

Sweden

+46 46 36 65 00

info.se@alfalaval.com

Australian supplier:

Alfa Laval Australia Pty Ltd

Locked Bag 40, Blacktown Business Centre

NSW - NSW-2148 Blacktown

Australia

Visit: 14 Healey Circuit, - NSW - NSW-2148 Huntingwood

Tel switchboard: +61 2 8822 2700 - Fax switchboard: +61 2 8822 2799

www.alfalaval.com.au australia.info@alfalaval.com

### · Further information obtainable from:

For further questions regarding the safety data sheet, please contact your local Alfa Laval Sales Company which you find at www.alfalaval.com or in section 16 "Other Information" in the end of the safety data sheet

## Emergency telephone number:

Call 000 or 112 and ask for poison information.

Australian Poisons Information Centre Tel:13 11 26

## 2 Hazard(s) Identification

## · Classification of the substance or mixture

Self-heat. 1 H251 Self-heating: may catch fire.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



· Signal word Danger

(Contd. on page 2)



Page 2/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 1)

## · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)

## Hazard statements

H251 Self-heating: may catch fire.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

### · Precautionary statements

P280 Wear protective clothing / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P413 Store bulk masses greater than 1 kg at temperatures not exceeding 5°C.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** The product is not, nor contains, a substance that is, PBT.
- · **vPvB:** The product is not, nor contains a substance that is, vPvB.

## 3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

| · Description:          |  |         |  |
|-------------------------|--|---------|--|
|                         | Non-volatile amide (hydrazide)   |         |  |
| CAS: 112945-52-5        | Amorphous silica, crystalline free, synthetic  | 2.5-10% |  |
| · Dangerous components: |  |         |  |
|                         | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number<br>average molecular weight ≤ 700)<br>Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin<br>Sens. 1, H317 | 50-100% |  |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **4 First Aid Measures**

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

### After inhalation:

Supply fresh air.

Seek medical treatment if symptoms persists.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

(Contd. on page 3)



Page 3/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

· After eye contact:

(Contd. of page 2)

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If symptoms persist consult a doctor.

· After swallowing:

Rinse the mouth with water.

If symptoms persist consult a doctor.

Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **5 Fire Fighting Measures**

Extinguishing media

· Suitable extinguishing agents:

Water spray

Foam

Use fire extinguishing methods suitable to surrounding conditions.

· For safety reasons unsuitable extinguishing agents: Not applicable.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Hydrogen chloride (HCI)

Carbon monoxide and carbon dioxide

Aldehyde

- Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Formation of toxic gases is possible during heating or in case of fire.

## **6 Accidental Release Measures**

Personal precautions, protective equipment and emergency procedures

Absorb liquid components with liquid-binding material.

Keep away from ignition sources.

· Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

In case of seepage into the ground inform responsible authorities.

Send for recovery or disposal in suitable receptacles.

· Methods and material for containment and cleaning up: Pick up mechanically.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Page 4/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

See Section 13 for disposal information.

(Contd. of page 3)

## 7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Do not breathe vapour.

Avoid contact with skin and eyes.

Handle and open container with care.

Avoid release to the environment.

This material and its container must be disposed of in a safe way.

See Section 8 for information on personal protection equipment.

- Information about fire and explosion protection: Substance/product is self ignitable.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles:

Keep away from heat and direct sunlight.

Store in a cool location.

- · Information about storage in one common storage facility: Reacts with amines.
- · Further information about storage conditions: Keep container tightly sealed.
- · Recommended storage temperature: -18 4 °C
- · Specific end use(s)

. Adhesives

Only for trade users / technical specialists

## 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700: Hazard via inhalation route: Long time exposure: 12.25 mg/m³; Acute/short term exposure: 12.25 mg/m³. Repeated dose toxicity. Overall assessment factor: 12. Dose descriptor starting point: NOAEC.

· PNECs

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700: Aqua (freshwater): 0.006 mg/L, Assessment factor: 50, Extrapolation method: Assessment factor.

- Additional information: The lists valid during the making were used as basis.
- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Ensure that washing facilities are available at the work place.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 5)



Page 5/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 4)

Use only in well-ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

· Respiratory protection:

Not necessary if room is well-ventilated.

Filter P2 Filter P3

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

polymer laminate

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Limitation and supervision of exposure into the environment

Do not allow to enter sewers/ surface or ground water.

## **9 Physical and Chemical Properties**

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Highly viscous
Colour: Light beige
Odour: Characteristic
Odour threshold: Not determined.

· **pH-value:** Not applicable.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: Undetermined.

· Flash point: >107 °C

• **Flammability (solid, gas):** Self-heating; may catch fire.

(Contd. on page 6)



Page 6/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

|   | (Contd. of page 5                             |
|---|---|
| · Decomposition temperature:              | Not determined.                               |
| · Auto-ignition temperature:              | Not determined.                               |
| · Explosive properties:                   | Product does not present an explosion hazard. |
| · Explosion limits:                       |   |
| Lower:                                    | Not determined.                               |
| Upper:                                    | Not determined.                               |
| Oxidising properties                      | Not applicable.                               |
| · Vapour pressure:                        | Not determined.                               |
| · Density at 20 °C:                       | 1.24 g/cm <sup>3</sup>                        |
| · Relative density                        | Not determined.                               |
| · Vapour density                          | Not applicable.                               |
| Evaporation rate                          | Not applicable.                               |
| · Solubility in / Miscibility with        |   |
| water:                                    | Slightly soluble.                             |
| · Partition coefficient: n-octanol/water: | Not determined.                               |
| · Viscosity:                              |   |
| Dynamic at 20 °C:                         | 60,000 mPas (Brookfield)                      |
| Kinematic:                                | Not applicable.                               |
| · Other information                       | No further relevant information available.    |

# 10 Stability and Reactivity

- · Reactivity No further data; see item 7.
- · Chemical stability

Stable under normal temperature conditions and under recommended usage and storage.

- Thermal decomposition / conditions to be avoided: Exothermic thermal decomposition.
- Possibility of hazardous reactions

Exothermic polymerisation.

130°C

· Conditions to avoid

Keep away from heat.

Keep away from sources of ignition - No smoking.

Avoid hardening of large quantities in order to prevent premature reaction (exotherm) with high heat and smoke.

· Incompatible materials:

Reacts with amines.

Keep away from acids.

· Hazardous decomposition products:

Nitrogen oxides

Carbon monoxide and carbon dioxide

Aldehyde

Hydrogen chloride (HCI)

No further data; see item 7.

- AU



Page 7/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 6)

## 11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral NOAEL 750 mg/kg (Rat) (2 generations)

LD/LC50 values relevant for classification:

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700:

LD50: 13600 mg/kg, Oral Rat. LD50: >1200 mg/kg, Dermal Rat.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Dermal LD50 >1,600 mg/kg (Rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Irritant to skin and mucous membranes.

Causes skin irritation.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Irritation of skin Skin Corrosion/Irritation 4 (Rabbit) (OECD Guideline 404)

Serious eye damage/irritation

Irritating effect.

Causes serious eye irritation.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Irritation of eyes | Serious Eye Damage/Irritation | (Rabbit) (OECD Guideline 405)

- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

- Irritant
- Repeated dose toxicity Sensitising effect by skin contact is possible by prolonged exposure.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

## 12 Ecological Information

- · Toxicity
- · Aquatic toxicity:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

| CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) |
|--|
| LOED (00 b) A 75 mm/L (Fish) (OEOD Originalis - 000)   |

LC50 (96 h) 1.75 mg/L (Fish) (OECD Guideline 203)

EC50 220 mg/L (Algae) EC50 1.1-3.6 mg/L (Daphnia)

Persistence and degradability No further relevant information available.

(Contd. on page 8)



Page 8/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 7)

- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- **Ecotoxical effects:**
- · Remark:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## **14 Transport information**

| · UN-Number<br>· ADG, IMDG, IATA | UN3088  |
|----------------------------------|---|
| · UN proper shipping name        |   |
| · ADĞ                            | 3088 SELF-HEATING SOLID, ORGANIC, N.O.S. (HYDRAZIDE), ENVIRONMENTALLY HAZARDOUS |
| ·IMDG                            | SELF-HEATING SOLID, ORGANIC, N.O.S. (HYDRAZIDE), MARINE POLLUTANT               |
| ·IATA                            | SELF-HEATÍNG SOLID, ORGANIC, N.O.S. (HYDRAZIDE)                                 |

- · Transport hazard class(es)
- · ADG, IMDG



Class 4.2 Substances liable to spontaneous combustion.

(Contd. on page 9)



Page 9/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

|  | (Contd. of page   |
|--|---|
| Label  | 4.2   |
| IATA   |   |
|  |   |
| Class  | 4.2 Substances liable to spontaneous combustion   |
| Label  | 4.2   |
| Packing group<br>ADG, IMDG, IATA                                   | II  |
| Environmental hazards:   | Environmentally hazardous substance, solid  |
| Marine pollutant:  | Yes   |
| Special marking (ADG):   | Symbol (fish and tree) Symbol (fish and tree)   |
| Special precautions for user                                       | Warning: Substances liable to spontaneou combustion.  |
| Hazard identification number (Kemler code)                         |   |
| EMS Number:  | F-A,S-J   |
| Stowage Category   | A   |
| Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable.   |
| Transport/Additional information:                                  |   |
| <del>:</del>   |   |
| Limited quantities (LQ)  | 0   |
| Transport category   | 2   |
| Tunnel restriction code  | D/E   |
| · IMDG<br>· Limited quantities (LQ)                                | 0   |
| · UN "Model Regulation":   | UN 3088 SELF-HEATING SOLID, ORGANIC<br>N.O.S. (HYDRAZIDE), 4.2, II<br>ENVIRONMENTALLY HAZARDOUS |

# 15 Regulatory information

 $^{\circ}$  Safety, health and environmental regulations/legislation specific for the substance or mixture

| · Australian Inventory of Industrial Chemicals                 |   |  |
|--|---|--|
|  | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq 700)$ |  |
| CAS: 112945-52-5   | Amorphous silica, crystalline free, synthetic   |  |
| · Standard for the Uniform Scheduling of Medicines and Poisons |   |  |
| None of the ingredients is listed.                             |   |  |
|  | (Contd. on page 10)   |  |



Page 10/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 9)

Australia: Priority Existing Chemicals

None of the ingredients is listed.

### · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





## · Signal word Danger

## · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)

### · Hazard statements

H251 Self-heating: may catch fire.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

#### · Precautionary statements

P280 Wear protective clothing / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P413 Store bulk masses greater than 1 kg at temperatures not exceeding 5°C.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

### · Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. LIMITATION OF LIABILITY

This document is only intended to be used as guidance as regards the risks of which we are aware that are associated with the product. Every individual who works with the product or in close proximity of it must receive suitable training. Individuals who come into contact with the product must be capable of using their own judgement as regards conditions or methods for handling, storing and using the product. Alfa Laval is not liable for demands, losses or damage of any kind that arise from flaws or deficiencies in this document or from using, handling, storing or disposing of the product unless it can be proven that Alfa Laval has acted in a grossly negligent manner. Beyond what has been agreed upon and specified in writing with Alfa Laval in the individual case, Alfa Laval makes no promises or assumes any liability, including but not limited to implicit guarantees regarding marketability or appropriateness in terms of both the information provided in this document and the product to which the information refers.

(Contd. on page 11)



Page 11/12

# **Safety Data Sheet** according to WHS Regulations

Version number 15 Revision: 18.02.2022 Printing date 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 10)

Please contact your local Alfa Laval Sales Company for further questions.

### Relevant phrases

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

· Department issuing SDS: Alfa Laval Sustainability Environment

### Contact:

Argentina: alfa.consulta@alfalaval.com Australia: australia.info@alfalaval.com Austria: info.mideurope@alfalaval.com Belgium: benelux.info@alfalaval.com Bolivia: alfa.consulta@alfalaval.com Brazil: alfalaval.br@alfalaval.com Bulgaria: bulgaria.info@alfalaval.com Canada: alfacan.info@alfalaval.com Chile: chile.informacion@alfalaval.com China: china.info@alfalaval.com

Colombia: info.colombia@alfalaval.com Croatia: hrvatska.info@alfalaval.com

Czech Republic: czechrepublic.info@alfalaval.com

Denmark: info.nordic.dk@alfalaval.com Egypt: alme.marketing@alfalaval.com Estonia: estonia.info@alfalaval.com Finland: info.fi@alfalaval.com

France: environnement@alfalaval.com Germany: info.mideurope@alfalaval.com Greece: greece.info@alfalaval.com Hungary: info.hu@alfalaval.com India: india.info@alfalaval.com Indonesia: alfalindo@alfalaval.com Israel: israel.info@alfalaval.com Italy: alfalaval.italia@alfalaval.com Japan: hp.alfajp@alfalaval.com Latvia: latvia.info@alfalaval.com Lithuania: lithuania.info@alfalaval.com Malaysia: malaysia.info@alfalaval.com Mexico: mexico.info@alfalaval.com

The Netherlands: benelux.info@alfalaval.com New Zealand: newzealand.info@alfalaval.com

Norway: info.no@alfalaval.com Peru: ventas.peru@alfalaval.com

Philippines: philippines.info@alfalaval.com

Poland: poland.info@alfalaval.com Portugal: portugal.info@alfalaval.com Qatar: alme.marketing@alfalaval.com Romania: romania.info@alfalaval.com Russia: moscow.response@alfalaval.com Singapore: al.singapore@alfalaval.com Slovak Republic: slovakia.info@alfalaval.com Slovenia: slovenija.info@alfalaval.com

South Africa: info.sa@alfalaval.com Spain: info.spain@alfalaval.com

(Contd. on page 12)



Page 12/12

# Safety Data Sheet according to WHS Regulations

Printing date 18.02.2022 Version number 15 Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 11)

Sweden: info.se@alfalaval.com

Switzerland: info.mideurope@alfalaval.com

Taiwan: taiwan.info@alfalaval.com Thailand: thailand.info@alfalaval.com Turkey: turkey@alfalaval.com

Ukraine: ukraine.info@alfalaval.com

United Arab Emirates: alme.marketing@alfalaval.com

United Kingdom: general.uk@alfalaval.com

United States: customerservice.usa@alfalaval.com

Venezuela: venezuela.info@alfalaval.com Vietnam: vietnam.info@alfalaval.com

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Self-heat. 1: Self-heating substances and mixtures - Category 1

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

· \* Data compared to the previous version altered.

- AU