

Page 1/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: GC6B / GC4

· Article number: 32220-3055-5

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Alfa Laval Technologies AB

SE-221 00 Lund

Sweden

+46 46 36 65 00

info.se@alfalaval.com

#### · Further information obtainable from:

For further questions regarding the safety data sheet, please contact your local Alfa Laval Sales Company which you find at www.alfalaval.com or in section 16 "Other Information" in the end of the safety data sheet

#### · 1.4 Emergency telephone number:

For immediate, life-threatening emergencies, call 999. For health advice and information (24h) dial 111 (NHS direct).

In Europe: Call 112 and ask for poison information.

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Self-heat. 1 H251 Self-heating: may catch fire.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### · 2.2 Label elements

## · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GH

· Signal word Danger

### · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

(Contd. on page 2)



Page 2/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 1)

#### · Hazard statements

H251 Self-heating: may catch fire.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

## **Precautionary statements**

P280 Wear protective clothing / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P413 Store bulk masses greater than 1 kg at temperatures not exceeding 5°C.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Additional information:

Contains 25 % of components with unknown hazards to the aquatic environment.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** The product is not, nor contains, a substance that is, PBT.
- · **vPvB:** The product is not, nor contains a substance that is, vPvB.

## **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

Description:			
Non-volatile amide (hydrazide)			
· Dangerous components:	· Dangerous components:		
NLP: 500-033-5 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)  Aquatic Chronic 2, H411; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205  Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %  Skin Irrit. 2; H315: C ≥ 5 %	50-100%	
	Amorphous silica, crystalline free, synthetic substance with a Community workplace exposure limit	2.5-10%	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

#### After inhalation:

Supply fresh air.

Seek medical treatment if symptoms persists.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Page 3/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 2)

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If symptoms persist consult a doctor.

After swallowing:

Rinse the mouth with water.

If symptoms persist consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Water spray

Foam

Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing agents: Not applicable.
- 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Hydrogen chloride (HCI)

Carbon monoxide and carbon dioxide

Aldehyde

- 5.3 Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Formation of toxic gases is possible during heating or in case of fire.

## **SECTION 6: Accidental release measures**

## · 6.1 Personal precautions, protective equipment and emergency procedures

Absorb liquid components with liquid-binding material.

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

In case of seepage into the ground inform responsible authorities.

Send for recovery or disposal in suitable receptacles.

- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Page 4/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 3)

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Do not breathe vapour.

Avoid contact with skin and eyes.

Handle and open container with care.

Avoid release to the environment.

This material and its container must be disposed of in a safe way.

See Section 8 for information on personal protection equipment.

- Information about fire and explosion protection: Substance/product is self ignitable.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Keep away from heat and direct sunlight.

Store in a cool location.

- · Information about storage in one common storage facility: Reacts with amines.
- · Further information about storage conditions: Keep container tightly sealed.
- · Recommended storage temperature: -18 4 °C
- · 7.3 Specific end use(s)

Adhesives

Only for trade users / technical specialists

#### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 112945-52-5 Amorphous silica, crystalline free, synthetic

CONTROL PARAMETERS (TWA) Short-term value: 6 mg/m<sup>3</sup>

Long-term value: 2.4 mg/m<sup>3</sup>

Silica, amorphous

#### · DNELs

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700: Hazard via inhalation route: Long time exposure: 12.25 mg/m³; Acute/short term exposure: 12.25 mg/m³. Repeated dose toxicity. Overall assessment factor: 12. Dose descriptor starting point: NOAEC.

· PNECs

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700: Aqua (freshwater): 0.006 mg/L, Assessment factor: 50, Extrapolation method: Assessment factor.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Ensure that washing facilities are available at the work place.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)



Page 5/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 4)

Avoid contact with the eyes and skin.

Use only in well-ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protection:

Not necessary if room is well-ventilated.

Filter P2 Filter P3

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

polymer laminate

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Environmental exposure controls Do not allow to enter sewers/ surface or ground water.

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

General Information

Colour: Light beige
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range Undetermined.

• Flammability Self-heating: may catch fire.

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.
 Flash point: >107 °C
 Auto-ignition temperature: Not determined.
 Decomposition temperature: Not determined.

(Contd. on page 6)



Page 6/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 5)

· **pH** Not applicable.

· Viscosity:

· Kinematic viscosity Not applicable.

• Dynamic at 20 °C: 60,000 mPas (Brookfield)

Solubility

· water: Slightly soluble.

Partition coefficient n-octanol/water (log

value) Not determined.

• Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Particle characteristics
 1.24 g/cm³
 Not determined.
 Not applicable.
 See item 3.

· 9.2 Other information

· Appearance:

· Form: Highly viscous

• Explosive properties: Product does not present an explosion hazard.

Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot applicable.Not applicable.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void

· Self-heating substances and mixtures

Self-heating: may catch fire.

Substances and mixtures, which emit

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void
Void
Void

## **SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further data; see item 7.
- · 10.2 Chemical stability

Stable under normal temperature conditions and under recommended usage and storage.

(Contd. on page 7)



Page 7/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 6)

· Thermal decomposition / conditions to be avoided: Exothermic thermal decomposition.

· 10.3 Possibility of hazardous reactions

Exothermic polymerisation.

130°C

#### · 10.4 Conditions to avoid

Keep away from heat.

Keep away from sources of ignition - No smoking.

Avoid hardening of large quantities in order to prevent premature reaction (exotherm) with high heat and smoke.

· 10.5 Incompatible materials:

Reacts with amines.

Keep away from acids.

10.6 Hazardous decomposition products:

Nitrogen oxides

Carbon monoxide and carbon dioxide

Aldehyde

Hydrogen chloride (HCI)

No further data; see item 7.

## **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## · Acute toxicity

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral NOAEL 750 mg/kg (Rat) (2 generations) 750 mg/kg/day

#### · LD/LC50 values relevant for classification:

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700:

LD50: 13600 mg/kg, Oral Rat.

LD50: >1200 mg/kg, Dermal Rat.

## CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Dermal LD50 >1,600 mg/kg (Rat)

### · Skin corrosion/irritation

Causes skin irritation.

## CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Irritation of skin	Skin Corrosion/Irritation	4 (Rabbit) (OECD Guideline 404)
		OECD Guideline 404 (Acute Dermal Irritation /
		Corrosion)
		Result: Slightly irritating.

## Serious eye damage/irritation

Causes serious eye irritation.

(Contd. on page 8)



Page 8/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

	(Contd. of page 7)
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number	
average mol	ecular weight ≤ 700)
Irritation of eyes Serious Eye D	amage/Irritation (Rabbit) (OECD Guideline 405) OECD Guideline 405 (Acute Eye Irritation / Corrosion) Result: Not irritating.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Repeated dose toxicity Sensitising effect by skin contact is possible by prolonged exposure.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

Endocrine disrupting properties from https://edlists.org

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS: 25068	CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700)	
LC50 (96 h)	0 (96 h) 1.75 mg/L (Fish) (OECD Guideline 203)	
	OECD Guideline 203 (Fish, Acute Toxicity Test), Oncorhynchus mykiss, 96 h.	
EC50	220 mg/L (Algae) Chlorophyta	
	· · ·	
EC50	1.1-3.6 mg/L (Daphnia) Daphnia magna	

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects No further relevant information available.
- · Remark:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

GB •



Page 9/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 8)

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

· yes European waste catalogue

The European Waste Catalogue (EWC) waste codes do not refer to product but to origin. The manufacturer is therefore unable to quote a waste code for products which are used in various industries. Any codes shown should be regarded as a recommendation to the user.

	rany course choine are regarded as a recommendation to the deci-
	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN3088
· 14.2 UN proper shipping name	
·ADR	3088 SELF-HEATING SOLID, ORGANIC, N.O.S
	(HYDRAZIDE). ENVIRONMENTALLY
	HAZARDOUS
· IMDG	SELF-HEATING SOLID, ORGANIC, N.O.S
	(HYDRAZIDE), MARINE POLLUTANT
·IATA	SELF-HEATING SOLID, ORGANIC, N.O.S
	(HYDRAZIDE)
· 14.3 Transport hazard class(es)	
. ,	
· ADR, IMDG	



Class 4.2 Substances liable to spontaneous combustion.

(Contd. on page 10)



Page 10/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

	(Contd. of page
Label	4.2
IATA	
Class	4.2 Substances liable to spontaneous combustion
Label	4.2
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Environmentally hazardous substance, solid
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Substances liable to spontaneou combustion.
Hazard identification number (Kemler code)	
EMS Number:	F-A,S-J
Stowage Category	A
14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
Transport/Additional information:	
· ADR	
Limited quantities (LQ)	0
Transport category	2
Tunnel restriction code	D/E
· IMDG · Limited quantities (LQ)	0
UN "Model Regulation":	UN 3088 SELF-HEATING SOLID, ORGANIC N.O.S. (HYDRAZIDE), 4.2, II ENVIRONMENTALLY HAZARDOUS

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) no.1907/2006 (REACH) EU regulation (EC) no 1272/2008 (CLP)

EC DIRECTIVE 2008/98/EC (waste)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

(Contd. on page 11)



Page 11/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 10)

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. LIMITATION OF LIABILITY

This document is only intended to be used as guidance as regards the risks of which we are aware that are associated with the product. Every individual who works with the product or in close proximity of it must receive suitable training. Individuals who come into contact with the product must be capable of using their own judgement as regards conditions or methods for handling, storing and using the product. Alfa Laval is not liable for demands, losses or damage of any kind that arise from flaws or deficiencies in this document or from using, handling, storing or disposing of the product unless it can be proven that Alfa Laval has acted in a grossly negligent manner. Beyond what has been agreed upon and specified in writing with Alfa Laval in the individual case, Alfa Laval makes no promises or assumes any liability, including but not limited to implicit guarantees regarding marketability or appropriateness in terms of both the information provided in this document and the product to which the information refers.

Please contact your local Alfa Laval Sales Company for further questions.

#### Relevant phrases

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Department issuing SDS: Alfa Laval Sustainability Environment

· Contact:

Argentina: alfa.consulta@alfalaval.com Australia: australia.info@alfalaval.com Austria: info.mideurope@alfalaval.com Belgium: benelux.info@alfalaval.com Bolivia: alfa.consulta@alfalaval.com Brazil: alfalaval.br@alfalaval.com

(Contd. on page 12)



Page 12/13

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 11)

Bulgaria: bulgaria.info@alfalaval.com Canada: alfacan.info@alfalaval.com Chile: chile.informacion@alfalaval.com China: china.info@alfalaval.com Colombia: info.colombia@alfalaval.com Croatia: hrvatska.info@alfalaval.com

Czech Republic: czechrepublic.info@alfalaval.com

Denmark: info.nordic.dk@alfalaval.com Egypt: alme.marketing@alfalaval.com Estonia: estonia.info@alfalaval.com Finland: info.fi@alfalaval.com

France: environnement@alfalaval.com
Germany: info.mideurope@alfalaval.com
Greece: greece.info@alfalaval.com
Hungary: info.hu@alfalaval.com
India: india.info@alfalaval.com
Indonesia: alfalindo@alfalaval.com
Israel: israel.info@alfalaval.com
Italy: alfalaval.italia@alfalaval.com
Japan: hp.alfajp@alfalaval.com
Latvia: latvia.info@alfalaval.com
Lithuania: lithuania.info@alfalaval.com
Malaysia: malaysia.info@alfalaval.com
Mexico: mexico.info@alfalaval.com

The Netherlands: benelux.info@alfalaval.com New Zealand: newzealand.info@alfalaval.com

Norway: info.no@alfalaval.com Peru: ventas.peru@alfalaval.com

Philippines: philippines.info@alfalaval.com

Poland: poland.info@alfalaval.com
Portugal: portugal.info@alfalaval.com
Qatar: alme.marketing@alfalaval.com
Romania: romania.info@alfalaval.com
Russia: moscow.response@alfalaval.com
Singapore: al.singapore@alfalaval.com
Slovak Republic: slovakia.info@alfalaval.com
Slovenia: slovenija.info@alfalaval.com

Slovenia: slovenija.info@alfalaval.com South Africa: info.sa@alfalaval.com Spain: info.spain@alfalaval.com Sweden: info.se@alfalaval.com

Switzerland: info.mideurope@alfalaval.com

Taiwan: taiwan.info@alfalaval.com Thailand: thailand.info@alfalaval.com Turkey: turkey@alfalaval.com Ukraine: ukraine.info@alfalaval.com

United Arab Emirates: alme.marketing@alfalaval.com

United Kingdom: general.uk@alfalaval.com

United States: customerservice.usa@alfalaval.com

Venezuela: venezuela.info@alfalaval.com Vietnam: vietnam.info@alfalaval.com • Date of previous version: 08.09.2020 • Version number of previous version: 14

(Contd. on page 13)



Page 13/13

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2022 Version number 15 (replaces version 14) Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 12)

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Self-heat. 1: Self-heating substances and mixtures – Category 1

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.