

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 23

Loctite 2701

SDS No. : 173107 V016.0 Revision: 31.08.2022 printing date: 21.02.2023 Replaces version from: 21.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite 2701

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use:

Anaerobic Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkeladhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

| Classification (CLP): | |
|--|------------|
| Skin sensitizer | Category 1 |
| H317 May cause an allergic skin reaction. | |
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation. | |
| Specific target organ toxicity - single exposure | Category 3 |
| H335 May cause respiratory irritation. | |
| Target organ: respiratory tract irritation | |

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Hydroxypropyl methacrylate

| | 2,2'-Ethylenedioxydiethyl dimethacrylate |
|--|--|
| | Methacryloyloxyethyl succinate Cumene hydroperoxide Acetic acid, 2-phenylhydrazide 2-Hydroxyethyl methacrylate |
| | methyl methacrylate |
| | Propylene glycol dimethacrylate |
| | |
| Signal word: | Warning |
| Hazard statement: | H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. |
| Precautionary statement: | "***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.*** |
| Precautionary statement: Prevention | P261 Avoid breathing vapors. P280 Wear protective gloves. |
| Precautionary statement: Response | P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. |

2.3. Other hazards

None if used properly. Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. Non corrosive to eyes according to test method OECD 438 or based on analogy to similar products tested.

Following substances are present in a concentration >= 0,1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number | | Classification | | Add. |
|--|--------------|--|---|-------------|
| EC Number | | | Specific Conc. Limits, M- factors and ATEs | Information |
| REACH-Reg No. | | | | |
| Hydroxypropyl methacrylate | 25- 50 % | Skin Sens. 1, H317 | | |
| 27813-02-1 248-666-3 | | Eye Irrit. 2, H319 | | |
| 248-000-5 01-2119490226-37 | | | | |
| | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate | 5- < 10 % | Skin Sens. 1B, H317 | dermal:ATE = > 5.000 mg/kg inhalation:ATE = 28,17 | |
| 109-16-0 | | | mg/l;dust/mist | |
| 203-652-6 | | | | |
| 01-2119969287-21 | | | | |
| Methacryloyloxyethyl succinate | 1-< 3 % | Skin Sens. 1, H317 | | |
| 20882-04-6 244-096-4 | | Eye Dam. 1, H318 | | |
| 01-2120137902-58 | | | | |
| | 0.05 | | | |
| Cumene hydroperoxide 80-15-9 | 0,25-< 2,5 % | STOT RE 2, H373 Skin Corr. 1B, H314 | Skin Irrit. 2; H315; C 3 - < 10 % Eye Dam. 1; H318; C 3 - < 10 % | |
| 201-254-7 | | Acute Tox. 2, Inhalation, H330 | Eye Irrit. 2; H319; C 1 - < 3 % | |
| 01-2119475796-19 | | Aquatic Chronic 2, H411 | Skin Corr. 1B; H314; C >= 10 % STOT SE 3; H335; C >= 1 % | |
| | | Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 | ===== | |
| | | Org. Perox. E, H242 | dermal:ATE = 1.100 mg/kg | |
| | | STOT SE 3, H335 | | |
| methacrylic acid | 0,1-< 1 % | Acute Tox. 4, Oral, H302 | STOT SE 3; H335; C >= 1 % | |
| 79-41-4 | -, | Acute Tox. 3, Dermal, H311 | | |
| 201-204-4 01-2119463884-26 | | Acute Tox. 4, Inhalation, H332 | dermal:ATE = 500 mg/kg | |
| 01-2119403884-20 | | Skin Corr. 1A, H314 Eye Dam. 1, H318 | inhalation:ATE = 3,61 mg/l; | |
| | | STOT SE 3, H335 | | |
| Asstistatid 2 should be descide | 0.1-< 1 % | | | |
| Acetic acid, 2-phenylhydrazide 114-83-0 | 0,1-< 1 % | Acute Tox. 3, Oral, H301 Skin Irrit. 2, H315 | | |
| 204-055-3 | | Skin Sens. 1, H317 | | |
| | | Eye Irrit. 2, H319 | | |
| | | STOT SE 3, Inhalation, H335 Carc. 2, H351 | | |
| | | | | |
| 2-Hydroxyethyl methacrylate 868-77-9 | 0,1-<1% | Skin Irrit. 2, H315 Skin Sens. 1, H317 | | |
| 212-782-2 | | Eye Irrit. 2, H319 | | |
| 01-2119490169-29 | | | | |
| methyl methacrylate | 0,1-< 1 % | Flam. Liq. 2, H225 | STOT SE 3; H335; C >= 10 % | EU OEL |
| 80-62-6 | | STOT SE 3, H335 | | |
| 201-297-1 01-2119452498-28 | | Skin Irrit. 2, H315 Skin Sens. 1, H317 | | |
| 01 211)+52+70 20 | | Skin Sens. 1, H517 | | |
| Propylene glycol dimethacrylate | 0,1-< 1 % | STOT SE 3, H335 | | |
| 7559-82-2 | | Skin Sens. 1B, H317 Aquatic Chronic 3, H412 | | |
| | | Aquate Chronic 5, 11412 | | |

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media Suitable extinguishing media: Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons: None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Ensure adequate ventilation. Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas. Avoid skin and eye contact. Prolonged or repeated skin contact should be avoided See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

7.3. Specific end use(s)

Anaerobic Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

| Ingredient [Regulated substance] | ррт | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|--------------------------------------|---|-----------------|
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 20 | 72 | Time Weighted Average (TWA): | | EH40 WEL |
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 40 | 143 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | 208 | Time Weighted Average (TWA): | | EH40 WEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | Indicative | ECTLV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative | ECTLV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | 416 | Short Term Exposure Limit (STEL): | 15 minutes | EH40 WEL |

Occupational Exposure Limits

Valid for

Ireland

| Ingredient [Regulated substance] | ррт | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|--------------------------------------|---|-----------------|
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 20 | 70 | Time Weighted Average (TWA): | | IR_OEL |
| Methacrylic acid 79-41-4 [METHACRYLIC ACID] | 40 | 140 | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | Indicative | ECTLV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 50 | | Time Weighted Average (TWA): | Indicative | ECTLV |
| Methyl methacrylate 80-62-6 [METHYL METHACRYLATE] | 100 | | Short Term Exposure Limit (STEL): | 15 minutes Indicative OELV | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental I | Exposure | Value | | | | Remarks |
|--|------------------------------------|----------|------------------------|-----|-----------------|--------|-------------------------------------|
| | | period | | | - | | |
| Methacrylic acid, monoester with propane- | 0,000 | | mg/l 0,904 mg/l | ppm | mg/kg | others | |
| 1,2-diol 27813-02-1 | aqua (freshwater) | | | | | | |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | aqua (marine water) | | 0,904 mg/l | | | | |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | aqua (intermittent releases) | | 0,972 mg/l | | | | |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | sediment (freshwater) | | | | 6,28 mg/kg | | |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | sediment (marine water) | | | | 6,28 mg/kg | | |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | Soil | | | | 0,727 mg/kg | | |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | Marine water - intermittent | | 0,972 mg/l | | | | |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | Air | | | | | | no hazard identified |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | Predator | | | | | | no potential for bioaccumulation |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (freshwater) | | 0,164 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (marine water) | | 0,0164 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | aqua (intermittent releases) | | 0,164 mg/l | | | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sediment (freshwater) | | | | 1,85 mg/kg | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sediment (marine water) | | | | 0,185 mg/kg | | |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 2,2'-Ethylenedioxydiethyl dimethacrylate | Soil | | | | 0,274 mg/kg | | no hazard identified |
| 2,2 -Entylenedioxydiethyl dimethacrylate 109-16-0 2,2'-Ethylenedioxydiethyl dimethacrylate | Predator | | | | | | no potential for |
| 109-16-0 .alpha.,.alphaDimethylbenzyl | aqua | | 0,0031 | | | | bioaccumulation |
| hydroperoxide 80-15-9 | (freshwater) | | mg/l | | | | |
| .alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9 | aqua (intermittent releases) | | 0,031 mg/l | | | | |
| .alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9 | aqua (marine water) | | 0,00031 mg/l | | | | |
| .alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9 | sewage treatment plant (STP) | | 0,35 mg/l | | | | |
| .alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9 | sediment (freshwater) | | | | 0,023 mg/kg | | |
| .alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9 | sediment (marine water) | | | | 0,0023 mg/kg | | |
| .alpha.,.alphaDimethylbenzyl hydroperoxide | Soil | | | | 0,0029 mg/kg | | |

| 80-15-9 | | 1 1 | | I |
|-----------------------------|--------------------------|------------|------------|------------------|
| methacrylic acid | aqua | 0,82 mg/l | | |
| 79-41-4 | (freshwater) | | | |
| methacrylic acid | aqua (marine | 0,82 mg/l | | |
| 79-41-4 | water) | | | |
| methacrylic acid | sewage | 10 mg/l | | |
| 79-41-4 | treatment plant (STP) | | | |
| methacrylic acid | aqua | 0,82 mg/l | | |
| 79-41-4 | (intermittent | | | |
| | releases) | | | |
| methacrylic acid | Soil | | 1,2 mg/kg | |
| 79-41-4 | | | | |
| 2-Hydroxyethyl methacrylate | aqua | 0,482 mg/l | | |
| 868-77-9 | (freshwater) | | | |
| 2-Hydroxyethyl methacrylate | aqua (marine | 0,482 mg/l | | |
| 868-77-9 | water) | | | |
| 2-Hydroxyethyl methacrylate | sewage | 10 mg/l | | |
| 868-77-9 | treatment plant | | | |
| | (STP) | | | |
| 2-Hydroxyethyl methacrylate | aqua | 1 mg/l | | |
| 868-77-9 | (intermittent | | | |
| | releases) | | | |
| 2-Hydroxyethyl methacrylate | sediment | | 3,79 mg/kg | |
| 868-77-9 | (freshwater) | | | |
| 2-Hydroxyethyl methacrylate | sediment | | 3,79 mg/kg | |
| 868-77-9 | (marine water) | | | |
| 2-Hydroxyethyl methacrylate | Soil | | 0,476 | |
| 868-77-9 | | | mg/kg | |
| 2-Hydroxyethyl methacrylate | Predator | | | no potential for |
| 868-77-9 | | | | bioaccumulation |
| 2-Hydroxyethyl methacrylate | Marine water - | 1 mg/l | | |
| 868-77-9 | intermittent | | | |
| methyl methacrylate | aqua | 0,94 mg/l | | |
| 80-62-6 | (freshwater) | | | |
| methyl methacrylate | aqua (marine | 0,94 mg/l | | |
| 80-62-6 | water) | | | |
| methyl methacrylate | aqua | 0,94 mg/l | | |
| 80-62-6 | (intermittent | | | |
| | releases) | | | |
| methyl methacrylate | sewage | 10 mg/l | | |
| 80-62-6 | treatment plant | | | |
| | (STP) | | | |
| methyl methacrylate | sediment | | 5,74 mg/kg | |
| 80-62-6 | (freshwater) | | | |
| methyl methacrylate | Soil | | 1,47 mg/kg | |
| 80-62-6 | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|---------------------|----------------------|---|------------------|-------------|-------------------------------------|
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | Workers | dermal | Long term exposure - systemic effects | | 4,2 mg/kg | no hazard identified |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | Workers | Inhalation | Long term exposure - systemic effects | | 14,7 mg/m3 | no hazard identified |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | General population | dermal | Long term exposure - systemic effects | | 2,5 mg/kg | no hazard identified |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | General population | Inhalation | Long term exposure - systemic effects | | 8,8 mg/m3 | no hazard identified |
| Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1 | General population | oral | Long term exposure - systemic effects | | 2,5 mg/kg | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Workers | inhalation | Long term exposure - systemic effects | | 48,5 mg/m3 | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Workers | dermal | Long term exposure - systemic effects | | 13,9 mg/kg | no hazard identified |
| 2.2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | General population | inhalation | Long term exposure - systemic effects | | 14,5 mg/m3 | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | General population | dermal | Long term exposure - systemic effects | | 8,33 mg/kg | no hazard identified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | General population | oral | Long term exposure - systemic effects | | 8,33 mg/kg | no hazard identified |
| .alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9 | Workers | inhalation | Long term exposure - systemic effects | | 6 mg/m3 | |
| methacrylic acid 79-41-4 | Workers | Inhalation | Long term exposure - local effects | | 88 mg/m3 | |
| methacrylic acid 79-41-4 | Workers | Inhalation | Long term exposure - systemic effects | | 29,6 mg/m3 | |
| methacrylic acid 79-41-4 | Workers | dermal | Long term exposure - systemic effects | | 4,25 mg/kg | |
| methacrylic acid 79-41-4 | General population | Inhalation | Long term exposure - local effects | | 6,55 mg/m3 | |
| methacrylic acid 79-41-4 | General population | Inhalation | Long term exposure - systemic effects | | 6,3 mg/m3 | |
| methacrylic acid 79-41-4 | General population | dermal | Long term exposure - systemic effects | | 2,55 mg/kg | |
| 2-Hydroxyethyl methacrylate 868-77-9 | Workers | dermal | Long term exposure - systemic effects | | 1,3 mg/kg | no potential for bioaccumulation |
| 2-Hydroxyethyl methacrylate 868-77-9 | Workers | Inhalation | Long term exposure - systemic effects | | 4,9 mg/m3 | no potential for bioaccumulation |
| 2-Hydroxyethyl methacrylate 868-77-9 | General population | dermal | Long term exposure - systemic effects | | 0,83 mg/kg | no potential for bioaccumulation |
| 2-Hydroxyethyl methacrylate 868-77-9 | General population | Inhalation | Long term exposure - systemic effects | | 2,9 mg/m3 | no potential for bioaccumulation |
| 2-Hydroxyethyl methacrylate 868-77-9 | General population | oral | Long term exposure - systemic effects | | 0,83 mg/kg | no potential for bioaccumulation |
| methyl methacrylate 80-62-6 | Workers | dermal | Acute/short term exposure - local effects | | 1,5 mg/cm2 | |
| methyl methacrylate 80-62-6 | Workers | dermal | Long term exposure - | | 13,67 mg/kg | |

| | | | systemic effects | | |
|--------------------------------|-----------------------|------------|---|------------|--|
| methyl methacrylate 80-62-6 | Workers | Inhalation | Long term exposure - systemic effects | 208 mg/m3 | |
| methyl methacrylate 80-62-6 | Workers | dermal | Long term exposure - local effects | 1,5 mg/cm2 | |
| methyl methacrylate 80-62-6 | Workers | Inhalation | Long term exposure - local effects | 208 mg/m3 | |
| methyl methacrylate 80-62-6 | General population | dermal | Acute/short term exposure - local effects | 1,5 mg/cm2 | |
| methyl methacrylate 80-62-6 | General population | dermal | Long term exposure - systemic effects | 8,2 mg/kg | |
| methyl methacrylate 80-62-6 | General population | Inhalation | Long term exposure - systemic effects | 74,3 mg/m3 | |
| methyl methacrylate 80-62-6 | General population | dermal | Long term exposure - local effects | 1,5 mg/cm2 | |
| methyl methacrylate 80-62-6 | General population | Inhalation | Long term exposure - local effects | 104 mg/m3 | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | liquid |
|--|--|
| Delivery form | Currently under determination |
| Colour | green |
| Odor | mild |
| Melting point | Currently under determination |
| Initial boiling point | > 149,0 °C (> 300.2 °F)None |
| Flammability | Currently under determination |
| Explosive limits | Currently under determination |
| Flash point | > 93,00 °C (> 199.4 °F) |
| Auto-ignition temperature | Currently under determination |
| Decomposition temperature | Currently under determination |
| рН | Not applicable, Product reacts with water. |
| Viscosity (kinematic) | Currently under determination |
| Solubility (qualitative) | Partially soluble |
| (Solvent: Water) | |
| Solubility (qualitative) | Miscible |
| (Solvent: Acetone) | |
| Partition coefficient: n-octanol/water | Currently under determination |
| Vapour pressure | 0,3000000 mbar |
| (20,0 °C (68 °F)) | |
| Density | 1,1 g/cm3 None |
| () | |
| Relative vapour density: | Not available. |
| Particle characteristics | Not applicable |
| | Product is a liquid |

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity Reacts with strong oxidants.

10.2. Chemical stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions See section reactivity

10.4. Conditions to avoid No decomposition if used according to specifications.

10.5. Incompatible materials See section reactivity.

10.6. Hazardous decomposition products carbon oxides.

SECTION 11: Toxicological information

General toxicological information:

Prolonged or repeated contact may cause skin irritation.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Hydroxypropyl methacrylate 27813-02-1 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | LD50 | 10.837 mg/kg | rat | not specified |
| Methacryloyloxyethyl succinate 20882-04-6 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |
| Cumene hydroperoxide 80-15-9 | LD50 | 382 mg/kg | rat | other guideline: |
| methacrylic acid 79-41-4 | LD50 | 1.320 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| Acetic acid, 2- phenylhydrazide 114-83-0 | LD50 | 270 mg/kg | rat | not specified |
| 2-Hydroxyethyl methacrylate 868-77-9 | LD50 | 5.564 mg/kg | rat | FDA Guideline |
| methyl methacrylate 80-62-6 | LD50 | 9.400 mg/kg | rat | not specified |
| Propylene glycol dimethacrylate 7559-82-2 | LD50 | 8.700 mg/kg | rat | FDA Guideline |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|--|----------------------|---------|--|
| Hydroxypropyl methacrylate 27813-02-1 | LD50 | > 5.000 mg/kg | rabbit | not specified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | Acute toxicity estimate (ATE) | > 5.000 mg/kg | | Expert judgement |
| Cumene hydroperoxide 80-15-9 | Acute toxicity estimate (ATE) | 1.100 mg/kg | | Expert judgement |
| methacrylic acid 79-41-4 | LD50 | 500 - 1.000 mg/kg | rabbit | Dermal Toxicity Screening |
| methacrylic acid 79-41-4 | Acute toxicity estimate (ATE) | 500 mg/kg | | Expert judgement |
| 2-Hydroxyethyl methacrylate 868-77-9 | LD50 | > 5.000 mg/kg | rabbit | not specified |
| methyl methacrylate 80-62-6 | LD50 | > 5.000 mg/kg | rabbit | not specified |
| Propylene glycol dimethacrylate 7559-82-2 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Test atmosphere | - | Species | Method |
|---------------------------|----------|------------|-----------------|------|---------|---------------------------|
| CAS-No. | type | | | time | | |
| 2,2'-Ethylenedioxydiethyl | Acute | 28,17 mg/l | dust/mist | | | Expert judgement |
| dimethacrylate | toxicity | | | | | |
| 109-16-0 | estimate | | | | | |
| | (ATE) | | | | | |
| Cumene hydroperoxide | LC50 | 1,370 mg/l | vapour | 4 h | rat | not specified |
| 80-15-9 | | | | | | |
| methacrylic acid | LC50 | > 3,6 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute |
| 79-41-4 | | | | | | Inhalation Toxicity) |
| methacrylic acid | Acute | 3,61 mg/l | | | | Expert judgement |
| 79-41-4 | toxicity | | | | | |
| | estimate | | | | | |
| | (ATE) | | | | | |
| methyl methacrylate | LC50 | 29,8 mg/l | vapour | 4 h | rat | not specified |
| 80-62-6 | | | | | | |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|------------------------|------------------|--|---|
| Hydroxypropyl methacrylate 27813-02-1 | not irritating | 24 h | rabbit | Draize Test |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | not irritating | 24 h | rabbit | Draize Test |
| Methacryloyloxyethyl succinate 20882-04-6 | not irritating | 0,25 h | Human, EPISKIIN™ Reconstituted Human Epidermis model | OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method) |
| Methacryloyloxyethyl succinate 20882-04-6 | Not Classified | 4 h | Human, EPISKIIN™ Reconstituted Human Epidermis model | OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method) |
| Cumene hydroperoxide 80-15-9 | corrosive | | rabbit | Draize Test |
| methacrylic acid 79-41-4 | corrosive | 3 min | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| 2-Hydroxyethyl methacrylate 868-77-9 | slightly irritating | 24 h | rabbit | Draize Test |
| Propylene glycol dimethacrylate 7559-82-2 | not irritating | 24 h | rabbit | FDA Guideline |

Serious eye damage/irritation:

Non corrosive to eyes according to test method OECD 438 or based on analogy to similar products tested.

| Hazardous substances | Result | Exposure | Species | Method |
|---|--|----------|----------------------------------|---|
| CAS-No. | | time | _ | |
| Hydroxypropyl methacrylate 27813-02-1 | Category 2B (mildly irritating to eyes) | | rabbit | Draize Test |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Methacryloyloxyethyl succinate 20882-04-6 | Category I | 10 min | Bovine, cornea, in vitro test | OECD Guideline 437 (BCOP) |
| methacrylic acid 79-41-4 | corrosive | | rabbit | Draize Test |
| 2-Hydroxyethyl methacrylate 868-77-9 | Category 2B (mildly irritating to eyes) | | rabbit | Draize Test |
| Propylene glycol dimethacrylate 7559-82-2 | not irritating | | rabbit | Draize Test |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---|-----------------|---------------------------------------|------------|--|
| Hydroxypropyl methacrylate 27813-02-1 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Hydroxypropyl methacrylate 27813-02-1 | sensitising | Guinea pig maximisation test | guinea pig | not specified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| methacrylic acid 79-41-4 | not sensitising | Buehler test | guinea pig | equivalent or similar to OECD Guideline 406 (Skin Sensitisation) |
| 2-Hydroxyethyl methacrylate 868-77-9 | not sensitising | Buehler test | guinea pig | Buehler test |
| 2-Hydroxyethyl methacrylate 868-77-9 | sensitising | Guinea pig maximisation test | guinea pig | Magnusson and Kligman Method |
| methyl methacrylate 80-62-6 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Propylene glycol dimethacrylate 7559-82-2 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---|----------|--|--|---------|--|
| Hydroxypropyl methacrylate 27813-02-1 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hydroxypropyl methacrylate 27813-02-1 | positive | in vitro mammalian chromosome aberration test | with and without | | Chromosome Aberration Test |
| Hydroxypropyl methacrylate 27813-02-1 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | negative | in vitro mammalian cell micronucleus test | with and without | | OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test) |
| Methacryloyloxyethyl succinate 20882-04-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Cumene hydroperoxide 80-15-9 | positive | bacterial reverse mutation assay (e.g Ames test) | without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| methacrylic acid 79-41-4 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2-Hydroxyethyl methacrylate 868-77-9 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2-Hydroxyethyl methacrylate 868-77-9 | positive | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| methyl methacrylate 80-62-6 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | not specified |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|---|------------------|----------------------|---|---------|-------------|---|
| Hydroxypropyl methacrylate 27813-02-1 | not carcinogenic | inhalation | 2 y 6 h/d, 5 d/w | rat | male | equivalent or similar OECD Guideline 451 (Carcinogenicity Studies) |
| methacrylic acid 79-41-4 | not carcinogenic | inhalation | 2 y | mouse | male/female | OECD Guideline 451 (Carcinogenicity Studies) |
| 2-Hydroxyethyl methacrylate 868-77-9 | not carcinogenic | inhalation | 2 y 6 h/d, 5 d/w | rat | female | equivalent or similar OECD Guideline 451 (Carcinogenicity Studies) |
| 2-Hydroxyethyl methacrylate 868-77-9 | not carcinogenic | inhalation | 2 y 6 h/d, 5 d/w | rat | male | equivalent or similar OECD Guideline 451 (Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---|--|-----------------------------|----------------------|---------|---|
| Hydroxypropyl methacrylate 27813-02-1 | NOAEL P 300 mg/kg NOAEL F1 1.000 mg/kg | screening | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOAEL P 400 mg/kg NOAEL F1 400 mg/kg | two- generation study | oral: gavage | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg | | oral: gavage | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| methacrylic acid 79-41-4 | NOAEL P 50 mg/kg NOAEL F1 400 mg/kg NOAEL F2 400 mg/kg | Two generation study | oral: gavage | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| 2-Hydroxyethyl methacrylate 868-77-9 | NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg | screening | oral: gavage | rat | equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---|-------------------|------------------------|--|---------|---|
| Hydroxypropyl methacrylate 27813-02-1 | NOAEL 300 mg/kg | oral: gavage | 49 d daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOAEL 0,352 mg/l | inhalation | 90 d 6 h/d, 5 d/w | rat | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | NOAEL 1.000 mg/kg | oral: gavage | daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Cumene hydroperoxide 80-15-9 | | inhalation: aerosol | 6 h/d 5 d/w | rat | not specified |
| methacrylic acid 79-41-4 | | inhalation | 90 d 6 h/d, 5 d/w | rat | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |
| 2-Hydroxyethyl methacrylate 868-77-9 | NOAEL 100 mg/kg | oral: gavage | 49 d daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | NOAEL 0,352 mg/l | inhalation | 90 d 6 h/d, 5 d/w | rat | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |
| methyl methacrylate 80-62-6 | LOAEL 2000 ppm | inhalation | 14 weeks 6 hrs/day, 5 days/wk | mouse | Dose Range Finding Study |
| methyl methacrylate 80-62-6 | NOAEL 1000 ppm | inhalation | 14 weeks 6 hrs/day, 5 days/wk | mouse | Dose Range Finding Study |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|-----------------------------|-------|------------|---------------|----------------------------|---------------------------|
| CAS-No. | type | | _ | | |
| Hydroxypropyl methacrylate | LC50 | 493 mg/l | 48 h | Leuciscus idus melanotus | DIN 38412-15 |
| 27813-02-1 | | | | | |
| 2,2'-Ethylenedioxydiethyl | LC50 | 16,4 mg/l | 96 h | Danio rerio | OECD Guideline 203 (Fish, |
| dimethacrylate | | | | | Acute Toxicity Test) |
| 109-16-0 | | | | | |
| Cumene hydroperoxide | LC50 | 3,9 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, |
| 80-15-9 | | | | | Acute Toxicity Test) |
| methacrylic acid | LC50 | 85 mg/l | 96 h | Salmo gairdneri (new name: | EPA OTS 797.1400 (Fish |
| 79-41-4 | | | | Oncorhynchus mykiss) | Acute Toxicity Test) |
| 2-Hydroxyethyl methacrylate | LC50 | > 100 mg/l | 96 h | Oryzias latipes | OECD Guideline 203 (Fish, |
| 868-77-9 | | | | | Acute Toxicity Test) |
| methyl methacrylate | LC50 | 350 mg/l | 96 h | Leuciscus idus | OECD Guideline 203 (Fish, |
| 80-62-6 | | | | | Acute Toxicity Test) |
| Propylene glycol | LC50 | 15,95 mg/l | 96 h | Danio rerio (reported as | OECD Guideline 203 (Fish, |
| dimethacrylate | | | | Brachydanio rerio) | Acute Toxicity Test) |
| 7559-82-2 | | | | | - |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|--------------|---------------|---------------|---|
| Hydroxypropyl methacrylate 27813-02-1 | EC50 | > 143 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Methacryloyloxyethyl succinate 20882-04-6 | EC50 | > 515,4 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Cumene hydroperoxide 80-15-9 | EC50 | 18,84 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| methacrylic acid 79-41-4 | EC50 | > 130 mg/l | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| 2-Hydroxyethyl methacrylate 868-77-9 | EC50 | 380 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| methyl methacrylate 80-62-6 | EC50 | 69 mg/l | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |
| Propylene glycol dimethacrylate 7559-82-2 | EC50 | 44,9 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-----------|---------------|---------------|--|
| Hydroxypropyl methacrylate 27813-02-1 | NOEC | 45,2 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | NOEC | 32 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | NOEC | 24,1 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

| methyl methacrylate 80-62-6 | NOEC | 37 mg/l | 21 d | 1 0 | OECD 211 (Daphnia magna, Reproduction Test) |
|---|------|-----------|------|-----|--|
| Propylene glycol dimethacrylate 7559-82-2 | NOEC | 5,05 mg/l | 21 d | 1 0 | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

| The mixture is classified based on calculation method referring | g to the classified substances present in the mixture. |
|---|--|

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-------------|---------------|--|--|
| Hydroxypropyl methacrylate 27813-02-1 | EC50 | > 97,2 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroxypropyl methacrylate 27813-02-1 | NOEC | > 97,2 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | EC50 | > 100 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | NOEC | 18,6 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Methacryloyloxyethyl succinate 20882-04-6 | EC50 | > 312 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Methacryloyloxyethyl succinate 20882-04-6 | NOEC | 21,1 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Cumene hydroperoxide 80-15-9 | EC50 | 3,1 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Cumene hydroperoxide 80-15-9 | NOEC | 1 mg/l | 72 h | Desmodesmus subspicatus (reported as Scenedesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methacrylic acid 79-41-4 | NOEC | 8,2 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methacrylic acid 79-41-4 | EC50 | 45 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | EC50 | 836 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | NOEC | 400 mg/l | 72 h | Selenastrum capricornutum OECD Guideline (new name: Pseudokirchneriella Growth Inhibitior subcapitata) | |
| methyl methacrylate 80-62-6 | EC50 | 170 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| methyl methacrylate 80-62-6 | NOEC | 100 mg/l | 96 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Propylene glycol dimethacrylate 7559-82-2 | EC50 | 17,3 mg/l | 72 h | Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Propylene glycol dimethacrylate 7559-82-2 | EC10 | 6,93 mg/l | 72 h | Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|---|-------|------------------|---------------|--|---|
| CAS-No. | type | | | | |
| Hydroxypropyl methacrylate 27813-02-1 | EC10 | 1.140 mg/l | 16 h | | not specified |
| Cumene hydroperoxide 80-15-9 | EC10 | 70 mg/l | 30 min | not specified | not specified |
| methacrylic acid 79-41-4 | EC10 | 100 mg/l | 17 h | | not specified |
| 2-Hydroxyethyl methacrylate 868-77-9 | EC0 | > 3.000 mg/l | 16 h | Pseudomonas fluorescens | other guideline: |
| methyl methacrylate 80-62-6 | EC20 | > 150 - 200 mg/l | 30 min | | ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge) |
| Propylene glycol dimethacrylate 7559-82-2 | EC50 | 570 mg/l | 3 h | activated sludge of a predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

12.2. Persistence and degradability

The product is not biodegradable.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|---|-----------|---------------|------------------|---|
| Hydroxypropyl methacrylate 27813-02-1 | readily biodegradable | aerobic | 94,2 % | 28 d | OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test) |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | readily biodegradable | aerobic | 85 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Methacryloyloxyethyl succinate 20882-04-6 | readily biodegradable, but failing 10-day window | aerobic | 80 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| Cumene hydroperoxide 80-15-9 | not readily biodegradable. | aerobic | 3 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| methacrylic acid 79-41-4 | inherently biodegradable | aerobic | 100 % | 14 d | OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test) |
| methacrylic acid 79-41-4 | readily biodegradable | aerobic | 86 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| 2-Hydroxyethyl methacrylate 868-77-9 | readily biodegradable | aerobic | 92 - 100 % | 14 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| methyl methacrylate 80-62-6 | readily biodegradable | aerobic | 94 % | 14 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| Propylene glycol dimethacrylate 7559-82-2 | not readily biodegradable. | aerobic | 69 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentratio n factor (BCF) | Exposure time | Temperature | Species | Method |
|---------------------------------|-----------------------------------|---------------|-------------|-------------|---------------------------------|
| Cumene hydroperoxide | 9,1 | | | calculation | OECD Guideline 305 |
| 80-15-9 | | | | | (Bioconcentration: Flow-through |
| | | | | | Fish Test) |

12.4. Mobility in soil

Cured adhesives are immobile.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|--------|-------------|--|
| Hydroxypropyl methacrylate 27813-02-1 | 0,97 | 20 °C | not specified |
| 2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 | 2,3 | | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Methacryloyloxyethyl succinate 20882-04-6 | 0,783 | 23 °C | EU Method A.8 (Partition Coefficient) |
| Cumene hydroperoxide 80-15-9 | 1,6 | 25 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| methacrylic acid 79-41-4 | 0,93 | 22 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| Acetic acid, 2- phenylhydrazide 114-83-0 | 0,74 | | not specified |
| 2-Hydroxyethyl methacrylate 868-77-9 | 0,42 | 25 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| methyl methacrylate 80-62-6 | 1,38 | 20 °C | other guideline: |
| Propylene glycol dimethacrylate 7559-82-2 | 2,63 | | other (calculated) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|--|--|
| | |
| Hydroxypropyl methacrylate | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 27813-02-1 | Bioaccumulative (vPvB) criteria. |
| 2,2'-Ethylenedioxydiethyl dimethacrylate | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 109-16-0 | Bioaccumulative (vPvB) criteria. |
| Cumene hydroperoxide | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 80-15-9 | Bioaccumulative (vPvB) criteria. |
| methacrylic acid | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 79-41-4 | Bioaccumulative (vPvB) criteria. |
| 2-Hydroxyethyl methacrylate | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 868-77-9 | Bioaccumulative (vPvB) criteria. |
| methyl methacrylate | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very |
| 80-62-6 | Bioaccumulative (vPvB) criteria. |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water. Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

| 14.1. | UN number or 1 | ID number |
|-------|-----------------|---|
| | ADR | Not dangerous goods |
| | RID | Not dangerous goods |
| | ADN | Not dangerous goods |
| | IMDG | Not dangerous goods |
| | IATA | Not dangerous goods |
| 14.2. | UN proper ship | ping name |
| | ADR | Not dangerous goods |
| | RID | Not dangerous goods |
| | ADN | Not dangerous goods |
| | IMDG | Not dangerous goods |
| | IATA | Not dangerous goods |
| 14.3. | Transport haza | rd class(es) |
| | ADR | Not dangerous goods |
| | RID | Not dangerous goods |
| | ADN | Not dangerous goods |
| | IMDG | Not dangerous goods |
| | IATA | Not dangerous goods |
| 14.4. | Packing group | |
| | ADR | Not dangerous goods |
| | RID | Not dangerous goods |
| | ADN | Not dangerous goods |
| | IMDG | Not dangerous goods |
| | IATA | Not dangerous goods |
| 14.5. | Environmental | hazards |
| | ADR | not applicable |
| | RID | not applicable |
| | ADN | not applicable |
| | IMDG | not applicable |
| | IATA | not applicable |
| 14.6. | Special precaut | ions for user |
| | ADR | not applicable |
| | RID | not applicable |
| | ADN | not applicable |
| | IMDG | not applicable |
| | IATA | not applicable |
| 14.7. | Maritime trans | port in bulk according to IMO instruments |
| | not applicable | |
| | | |
| | | |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable VOC content < 3 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows: H225 Highly flammable liquid and vapour. H242 Heating may cause a fire. H301 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H330 Fatal if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. ED: Substance identified as having endocrine disrupting properties EU OEL: Substance with a Union workplace exposure limit FUEXPLD 1. Substance listed in Annex L Reg (EC) No. 2019/1148

| $L \cup L \cap L \cap L \cup L$ | Substance listed in 7 linex 1, Reg (LC) 10. 2017/1140 |
|---------------------------------|--|
| EU EXPLD 2 | Substance listed in Annex II, Reg (EC) No. 2019/1148 |
| SVHC: | Substance of very high concern (REACH Candidate List) |
| PBT: | Substance fulfilling persistent, bioaccumulative and toxic criteria |
| PBT/vPvB: | Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very |
| | bioaccumulative criteria |
| vPvB: | Substance fulfilling very persistent and very bioaccumulative criteria |
| | |

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.