

Page 1/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

1 Identification

· Product identifier

· Trade name: Slide Laquer · Article number: 1899900-01

- · Application of the substance / the mixture Lubricant
- · Details of the supplier of the safety data sheet

· Supplier:

Alfa Laval Technologies AB

SE-221 00 Lund

Sweden

+46 46 36 65 00

info.se@alfalaval.com

· Information department:

For additional questions regarding safety data sheets please contact your local Alfa Laval Sales Company which you find on www.alfalaval.com or in safety data sheet under section 16: Other Information

· Emergency telephone number:

Call CHEMTREC

+1 703-741-5970 / 1-800-424-9300 CCN 844

2 Hazard(s) identification

· Classification of the substance or mixture

Eye Damage 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

calcium dihydroxide

· Hazard statements

H318 Causes serious eye damage.

· Precautionary statements

P280 Wear eye protection / face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

- Other hazards Prolonged and/or repeated skin contact may cause irritation.
- Results of PBT and vPvB assessment
- · PBT: The product is not, nor contains, a substance that is PBT
- · **vPvB:** The product is not, nor contains a substance that is, vPvB.

US



Page 2/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous com	ponents:	
CAS: 8042-47-5	White mineral oil, petroleum	30-60%
CAS: 1317-33-5	molybdenum disulphide	15-30%
	calcium dihydroxide Eye Damage 1, H318; Skin Irrititation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335	15-25%
CAS: 7782-42-5	Graphite	5-15%

4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Take off immediately all contaminated clothing.

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

After eye contact:

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes.

Prolonged and/or repeated skin contact may cause irritation.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Water haze

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Not applicable.
- · Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Metal oxides

Sulfur oxides (SOx)

(Contd. on page 3)



Page 3/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Cool endangered receptacles with water spray.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Send for recovery or disposal in suitable receptacles.

· Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
	molybdenum disulphide	50 mg/m³
CAS: 1305-62-0	calcium dihydroxide	15 mg/m³
· PAC-2:		
CAS: 1317-33-5	molybdenum disulphide	260 mg/m³
CAS: 1305-62-0	calcium dihydroxide	240 mg/m³
· PAC-3:		
CAS: 1317-33-5	molybdenum disulphide	1,600 mg/m³
CAS: 1305-62-0	calcium dihydroxide	1,500 mg/m³

7 Handling and storage

- Handling:
- · Precautions for safe handling

Ensure adequate ventilation

Avoid contact with skin and eyes.

Eye wash bottle or emergency eye wash fountain must be found in the work place When using do not eat, drink or smoke.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

· Information about storage in one common storage facility: Store away from oxidizing agents.

(Contd. on page 4)



Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

· Specific end use(s)

(Contd. of page 3)

Grease

Professional use only.

8 Exposure controls/personal protection

· Additional information about design of technical systems:

Use only in well-ventilated areas.

Eye wash bottle or emergency eye wash fountain must be found in the work place

· Control parameters

	ior paramotoro
· Com	ponents with limit values that require monitoring at the workplace:
CAS	: 8042-47-5 White mineral oil, petroleum
TLV	Short-term value: 10 mg/m³ Long-term value: 5 mg/m³
	Oil mist
CAS	: 1317-33-5 molybdenum disulphide
PEL	Long-term value: 15* mg/m³ *Total dust, as Mo
TLV	Long-term value: 10* 3** mg/m³ as Mo; *inhalable fraction ** respirable fraction
CAS	: 1305-62-0 calcium dihydroxide
PEL	Long-term value: 15* 5** mg/m³
DE.	*total dust **respirable fraction
	Long-term value: 5 mg/m³
TLV	Long-term value: 5 mg/m³
CAS	: 7782-42-5 Graphite
PEL	Long-term value: 15 mppcf* mg/m³ *impinger samples counted by light field techn.
REL	Long-term value: 2.5* mg/m³ *respirable dust
TLV	Long-term value: 2* mg/m³ all forms except graphite fibers;*resp. fraction

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of insufficient ventilation, wear suitable respiratory equipment.

Filter A

(Contd. on page 5)



Page 5/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Chloroprene rubber, CR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:



Tightly sealed goggles

- · Body protection: Wear protective clothing.
- · Limitation and supervision of exposure into the environment

Do not allow to enter sewers/ surface or ground water.

9 Physical and chemical properties

3 Filysical and chemical prope	Tues
· Information on basic physical and · General Information	chemical properties
· Appearance:	
Form:	Pasty
Color:	Black
· Odor:	Weak, characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	>200 °C (>392 °F)
· Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
	(Contd. on page 6)

– US



Page 6/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

		(Contd. of page
Explosion limits:		
Lower:	Not applicable.	
Upper:	Not applicable.	
Oxidizing properties	Not applicable.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.4 g/cm³ (11.683 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not determined.	
Partition coefficient (n-octanol/wa	ater): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Stable under normal temperature conditions and under recommended usage and storage.
- · Possibility of hazardous reactions Reacts with strong oxidizing agents.
- · Conditions to avoid High temperature
- · Incompatible materials: Store away from oxidizing agents.
- · Hazardous decomposition products: Formaldehyde

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/L	C50 values that	are relevant for classification:
Oral	LD50	>5,000 mg/kg (Rat)
CAS	: 8042-47-5 Whit	te mineral oil, petroleum
Derm	nal LD50	>2,000 mg/kg (Rabbit)
Inhal	ative LC50 (4 h)	>5 mg/L (Rat)
CAS	: 1317-33-5 moly	/bdenum disulphide
Oral	LD50	>2,000 mg/kg (Rat)
Derm	nal LD50	>2,000 mg/kg (Rat)
Inhal	ative LC50 (4 h)	>2.82 mg/L (Rat)

(Contd. on page 7)



Page 7/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

		(Contd. of page	6)
CAS: 130	5-62-0 calci	um dihydroxide	
Oral	LD50	>2,000 mg/kg (Rat) (OECD Test 425)	П
Dermal	LD50	>2,500 mg/kg (Rabbit) (OECD Test 402)	
CAS: 7782	2-42-5 Grap	hite	
Oral	LD50	>2,000 mg/kg (Rat) (OECD Test 401)	
Inhalative	LC50 (4 h)	>2 mg/L (Rat) (OECD Test 403)	

- Primary irritant effect:
- on the skin: Prolonged and / or repeated skin contact may cause irritation.
- on the eye:

Strong irritant with the danger of severe eye injury.

Irritating effect.

- · Sensitization: No sensitizing effects known.
- Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

CAS: 8042-47-5 White mineral oil, petrol		
LC50	>100 mg/L (Salmon trout) (OECD Test 2	(203)
EC50	>100 mg/L (Daphnia) (OECD TG 202)	
NOEC - No observed effect concentration	100 mg/l (Algae) (OECD TG 201)	
,	1 mg/l (Daphnia)	
	1 mg/l (Fish)	
CAS: 1317-33-5 molybdenum disulphide	e	
LC50 (96 h)	>100 mg/L (Fish)	
EC50	>100 mg/L (Daphnia)	
EC50 (72 h)	>100 mg/L (Algae)	
NOEC - No observed effect concentration	>10 mg/l (Daphnia)	
	>10 mg/l (Fish)	
CAS: 1305-62-0 calcium dihydroxide		
LC50 (96 h)	50.6 mg/L (Fish)	
EC50 (48 h)	49.1 mg/L (Daphnia) (OECD Test 202)	
EC50 (72 h)	184.57 mg/L (Algae) (OECD Test 201)	
NOEC - No observed effect concentration	32 mg/l (Daphnia)	
	1	(Contd. or



Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

		(Contd. of page 7)
CAS: 7782-42-5 Graphite		
LC50 (96 h)	>100 mg/L (Fish) (OECD Test 203)	
EC50	>100 mg/L (Daphnia) (OECD Test 202)	
EC50 (72 h)	>100 mg/L (Algae) (OECD Test 201)	
· Persistence and degradability		
CAS: 8042-47-5 White mineral oil, petro	leum	
Biodegradability 0-24 %		
Behavior in environmental systems:		
· Bioaccumulative potential		
CAS: 8042-47-5 White mineral oil, petro	leum	
Bioconcentration factor 1,900 (Fish)		
· Mobility in soil The product is not expected	ed to be mobile in soil.	

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Hand over to hazardous waste disposers.

Results of PBT and vPvB assessment

• **PBT:** The product is not, nor contains, a substance that is PBT • **vPvB:** The product is not, nor contains a substance that is, vPvB. • **Other adverse effects** No further relevant information available.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation:

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

· UN-Number · DOT, ADR, IMDG, IATA	The product is not classified as dangerous goods. Void
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not relevant. Void
· Transport hazard class(es)	The product is not classified as dangerous goods.
· DOT, ADR, ADN, IMDG, IATA · Class	Void
· Packing group · DOT, ADR, IMDG, IATA	Not applicable. Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.

US



Page 9/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

(Contd. of page 8)

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": Void

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) no.1907/2006 (REACH)

Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

(Contd. on page 10)



Page 10/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

(Contd. of page 9)

· Hazard-determining components of labeling:

calcium dihydroxide

· Hazard statements

H318 Causes serious eye damage.

· Precautionary statements

P280 Wear eye protection / face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. LIMITATION OF LIABILITY

This document is only intended to be used as guidance as regards the risks of which we are aware that are associated with the product. Every individual who works with the product or in close proximity of it must receive suitable training. Individuals who come into contact with the product must be capable of using their own judgement as regards conditions or methods for handling, storing and using the product. Alfa Laval is not liable for demands, losses or damage of any kind that arise from flaws or deficiencies in this document or from using, handling, storing or disposing of the product unless it can be proven that Alfa Laval has acted in a grossly negligent manner. Beyond what has been agreed upon and specified in writing with Alfa Laval in the individual case, Alfa Laval makes no promises or assumes any liability, including but not limited to implicit guarantees regarding marketability or appropriateness in terms of both the information provided in this document and the product to which the information refers.

Please contact your local Alfa Laval Sales Company for futher questions. www.alfalaval.com

- · Classification according to Regulation (EC) No 1272/2008 Bridging principles
- Department issuing SDS: Alfa Laval Corporate Standards & Regulatory Operations
- Contact:

Please contact your local Alfa Laval Sales Company for futher questions.

Argentina: alfa.consulta@alfalaval.com Australia: australia.info@alfalaval.com Austria: info.mideurope@alfalaval.com Belgium: benelux.info@alfalaval.com Bolivia: alfa.consulta@alfalaval.com Brazil: alfalaval.br@alfalaval.com Brazil: alfalaval.br@alfalaval.com Bulgaria: bulgaria.info@alfalaval.com Canada: alfacan.info@alfalaval.com Chile: chile.informacion@alfalaval.com China: china.info@alfalaval.com Colombia: info.colombia@alfalaval.com Croatia: hrvatska.info@alfalaval.com

Czech Republic: czechrepublic.info@alfalaval.com

Denmark: info.nordic.dk@alfalaval.com Egypt: alme.marketing@alfalaval.com Estonia: estonia.info@alfalaval.com Finland: info.fi@alfalaval.com

France: environnement@alfalaval.com Germany: info.mideurope@alfalaval.com

(Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

(Contd. of page 10)

Greece: greece.info@alfalaval.com
Hungary: info.hu@alfalaval.com
India: india.info@alfalaval.com
Indonesia: alfalindo@alfalaval.com
Israel: israel.info@alfalaval.com
Italy: alfalaval.italia@alfalaval.com
Japan: hp.alfajp@alfalaval.com
Latvia: latvia.info@alfalaval.com
Lithuania: lithuania.info@alfalaval.com
Malaysia: malaysia.info@alfalaval.com
Mexico: mexico.info@alfalaval.com

The Netherlands: benelux.info@alfalaval.com New Zealand: newzealand.info@alfalaval.com

Norway: info.no@alfalaval.com Peru: ventas.peru@alfalaval.com

Philippines: philippines.info@alfalaval.com Poland: poland.info@alfalaval.com

Portugal: portugal.info@alfalaval.com
Qatar: alme.marketing@alfalaval.com
Romania: romania.info@alfalaval.com
Russia: moscow.response@alfalaval.com
Singapore: al.singapore@alfalaval.com
Slovak Republic: slovakia.info@alfalaval.com

Slovenia: slovenija.info@alfalaval.com South Africa: info.sa@alfalaval.com Spain: info.spain@alfalaval.com Sweden: info.se@alfalaval.com

Switzerland: info.mideurope@alfalaval.com

Taiwan: taiwan.info@alfalaval.com Thailand: thailand.info@alfalaval.com Turkey: turkey@alfalaval.com Ukraine: ukraine.info@alfalaval.com

United Arab Emirates: alme.marketing@alfalaval.com

United Kingdom: general.uk@alfalaval.com

United States: customerservice.usa@alfalaval.com

Venezuela: venezuela.info@alfalaval.com Vietnam: vietnam.info@alfalaval.com

Date of preparation / last revision 05/31/2022 / 8

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

Skin Irrititation 2: Skin corrosion/irritation - Category 2

(Contd. on page 12)



Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/31/2022 Version 9 Reviewed on 05/31/2022

Trade name: Slide Laquer

(Contd. of page 11)

Eye Damage 1: Serious eye damage/eye irritation – Category 1
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.